

E.T.C AUSTRALIA

Tel:+61 08 9437 1313 Fax:+61 08 9437 1103



ETC IDB _ - 24/630 Integral Deadbreak Bushing

Up to 24kV, 630 Amp Class



ETC IDB_-24/630
Integral Deadbreak Bushing

Electrical Characteristics:

Voltage Ratings and Characteristics			
Description		kV	
Standard Voltage Class		24	
Maximum Rating Phase-to-phase		24	
AC 50 Hz 1 Minute Withstand		54	
DC 15 Minute Withstand		48	
BIL and Full Wave Crest		125	
20kV Partial Discharge		≤10pc	
Current Ratings and Characteristics			
Description	Amperes		
Continuous	630		
24 hour overload	1000		
	50,000 A rms symmetrical		
Short Time	for 0.3s 20,000 A rms		
	symmetrical for 4.0 s		
Electrical characteristics are in accordance with or			

Standard Packaging List:

standards.

1	Integral Deadbreak Bushing
2	4-Stud Clamp
3	Gasket
4	Silicone Lubricant
5	Cleaning Paper
6	Installation Instruction Sheet

exceed DIN 47636 and IEC 60502.4-1997s


General:


The ETC IDB_-24/630 Integral Deadreak Bushing combines the advantages of reliable integral design with the operating features required for three-phase switching. The bushing is designed for pad-mounted transformers, switchgear and other apparatus fliled with transformer oil, or an approved equivalent. It eliminates the insert-to-well interface present in bushing well and insert primary terminations.


The Bushing is molded with high quality insulating material. When mated with comparably rated products, it provides a fully shielded, submersible and separable connection for loadbreak operation.

The ETC IDB_-24/630 Integral Bushing includes two kinds. Type A is used in oil-insulated apparatus and type B is suitable for the air-insulated devices.

DIMENSIONS(mm)







4-Stud Clamp

E.T.C AUSTRALIA

Tel:+61 08 9437 1313 Fax:+61 08 9437 1103




630-11

Ordering Information:

To order a 630 amps, 24kV Integral Deadreak Bushing kit. Please refer to the CODE INFORMATION and select the proper Catalogue Number below.


Catalogue Number	Current Rating(A)	
ETC IDBA-24/630 ETC YTGZAC-24/630	630	
ETC IDBB-24/630 ETC YTGZBC-24/630	630	


Code Information:



Typical Arrangement:

- (1) 630A Integral Deadbreak Bushing + Shielded Connector
- (2) 630A Integral Deadbreak Bushing + Unshielded Connector





More Information for cable accessories, installation instructions, technical questions. Please contact your local Electrical Terminations & Components representative or visit our website http://www.etcaustralia.com.au